



540 SMOKE & ODOR DRY FALL COATING

Sentinel 540 Smoke & Odor Dry Fall Coating is a fast-drying product designed for high ceiling applications. 540 provides good light reflectancy and odor encapsulating and counteracting properties for trapping and covering up smoke and other odors. When sprayed on ceiling heights of 15' or more, overspray will dry before reaching the floor and can be vacuumed or swept up.

Application Information (Always follow product label instructions for best results)

Material Preparation:

Use on steel roofing, brick, concrete, wood, plaster, drywall or similar substrated. Thoroughly stir and mix coating to achieve an even consistency for spraying. Product must be sprayed, not brushed or rolled. Do NOT thin Sentinel 540 with water or solvents. **This product must not be allowed to freeze. Apply in temperatures above 50° F.**

Application Environment:

Apply in an environment greater than 50°F and less than 50% relative humidity.

Surface Preparation:

Remove all loose paint and clean surfaces of all dirt, dust, oil, grease, wax, rust or other contaminants. Allow all new masonry surfaces, plaster or drywall to cure before coating

Primers:

Sentinel 540 Dry Fall Coating can be applied on most building materials without priming. **DO NOT USE ON UNPRIMED METAL SURFACES.** When priming is necessary, prime with Sentinel Stain Blocking Primer.

Tinting:

Sentinel 540 Dry Fall Coating may be tinted with up to 2 oz. of colorant/per gallon.

Product Application:

All surfaces must be clean and completely dry before applying. For airless application, use a .015 -.021 tip. Do NOT brush or roll. When spraying keep spray gun close to the surface so the coating does not dry before reaching the substrate being coated.

Dry Time:

This product will be dry to the touch in 30 minutes at 77°F and 50% RH. Allow 1 hour before recoating.

Coverage:

Applied at 5 - 7 mils wet.
Non-Porous Surfaces: 125 - 300 Sq.ft per gallon
Porous Surfaces: 75 - 250 Sq.ft per gallon

Warranty:

Use strictly in accordance with instructions for use. Buyer assumes all responsibility for safety and use not in accordance with label instructions. Seller cannot control user's handling, use, or effect of use and therefore makes no warranty, expressed or implied, no accepts any direct or consequential damages beyond the purchase price.

SPECIFICATIONS

Physical State:	Liquid
Appearance:	Opaque
Color:	White
Odor:	Characteristic
pH:	8.25 - 9.0
Flash Point:	>199.4°F
V.O.C. Content:	<5 g/L (calc.)*
Viscosity:	105 - 115 KU
% Solids by Volume:	31.12%
Density:	10.7 pounds/gallon
Gloss:	Flat
Shelf Life:	36 Months



800-373-0633 or www.senpro.com

Sentinel Products, Inc. / 8901 Wyoming Avenue North, Brooklyn Park, MN 55445