

F O R M U L A



STAIN BLOCKING PRIMER

Multi-Surface Sealer/Primer
Stain Blocking Formula
Traps Odors



5 Gallons
(18.927L)

F O R M U L A



Multi-Surface Sealer/Primer
Stain Blocking Formula
Traps Odors

PRODUCT DESCRIPTION

Sentinel SBP Stain Blocking Primer is a zero V.O.C.*, water-based, low odor, fast drying primer designed to block tannin and water stains from bleeding through while prepping the surface for a topcoat. Sentinel SBP can be used on a number of surfaces including wall board, wood, plaster, stucco, and concrete. Sentinel SBP is not recommended for flooring or below grade applications.

WARRANTY NOTICE

Use strictly in accordance with instructions for use. Buyer assumes all responsibility for safety and use not in accordance with label instructions. Seller cannot control user's handling, use, or effect of use and therefore makes no warranty, expressed or implied, nor accepts any direct or consequential damages beyond the purchase price.

WARNING!

If you scrape, sand, or remove old paint, you may remove lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRECAUTIONS & FIRST AID



DANGER

Contains: Titanium dioxide, Calcium Carbonate, Sodium diocylsulfosuccinate, 2-aminoethanol, Crystalline Silica

HAZARD STATEMENTS: Causes serious eye irritation. May cause cancer (inhalation of dust). May cause damage to lungs through prolonged and repeated exposure to dust.

PRECAUTIONARY STATEMENTS: Do not breathe dust. Wash hands thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear eye protection, protective clothing, protective gloves, face protection. Use personal protective equipment as required. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical advice. Get medical advice/attention if you feel unwell. Store locked up. Dispose of contents/container to licensed waste handling facility. **FIRST AID NOT FOUND IN PRECAUTIONARY STATEMENTS:** IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if breathing is affected. If breathing is difficult, supply oxygen. IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. If irritation develops or persists, get medical attention. IF SWALLOWED: Rinse mouth thoroughly. Do not induce vomiting without advice from poison control center or medical professional. Seek medical attention. **HANDLING AND STORAGE:** Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Keep container closed when not in use. Store in dry, well-ventilated area. Keep container tightly closed in original container protected from sunlight. Keep from freezing. Store locked up.

INSTRUCTIONS

SURFACE PREPARATION

Sentinel SBP Stain Blocking Primer is a zero V.O.C.*, water-based, low odor, fast drying primer designed to block tannin and water stains from bleeding through while prepping the surface for a topcoat. Sentinel SBP can be used on a number of surfaces including wall board, wood, plaster, stucco, and concrete. Sentinel SBP is not recommended for flooring or below grade applications.

Surfaces must be clean and dry. Remove all dust, dirt, mold, mildew, efflorescence and other residues prior to application. Masonry, sheetrock and newly plastered walls must be allowed to adequately cure prior to application. Clean smoke damaged surfaces thoroughly prior to application.

DIRECTIONS FOR USE

Apply Sentinel SBP with a brush, roller, or airless sprayer with a .015 - .020 tip. Apply a uniform coating of 4.0 - 5.0 wet mils over all desired surfaces. A second coat may be necessary for certain heavy stain applications.

COVERAGE

On smooth surfaces, approximately 300-400 sq. ft. of coverage per gallon. Expect slightly less coverage on rough surfaces. Actual coverage will vary depending upon application method, surface texture, and porosity.

THINNING

Sentinel SBP Stain Blocking Primer is ready to use and should not be thinned with water or solvents.

DRY TIME

Fully cured in 24 hours at 75°F and 50% relative humidity or lower. 2 or more coats may be required. SBP may be recoated in 2 hours under most environmental conditions. Allow for longer drying times in areas of high humidity or dampness.

CLEAN UP

Clean painting equipment with warm soapy water while product is still wet. Any spills or splatters should be cleaned up immediately with a wet, soapy cloth. Dried coating may be removed using Sentinel 206 PeroxyStrip Paint and Coatings Stripper or other commercially available paint strippers suitable for water based paints.



WARNING: This product can expose you to chemicals including Titanium Dioxide, which are known to the state of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

REFER TO SDS FOR MORE INFORMATION
FOR INDUSTRIAL USE ONLY
KEEP OUT OF REACH OF CHILDREN

For special instructions or additional information contact
Sentinel at: 800-373-0633 or visit us at www.senpro.com



Sentinel Products Inc.
Brooklyn Park, MN 55445
800-373-0633
www.senpro.com

